DOOSAN

CRAWLER EXCAVATOR

NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- 20' 6" Boom, 10' 2" Arm
- 31.5" (800 mm) Shoes, rollers (2 upper/9 lower)
- 4 Power Modes / 4 Work Modes
- Telematics 3 Year Subscription
- Options Straight Travel, 2 way Aux. Hydraulic Pedal,
 Diesel Powered Coolant Heater, Plug Heater, Cab Guarding,
 Additional Work Lamps, Rotate Circuit Piping"

NEW MODEL OVERVIEW	DX300LC-5
Rated Power — Gross (HP per SAE J1995)	271 hp (202 kW) @ 1,800 rpm
Operating Weight	68,961 lb. (31 280 kg)
Max. Digging Depth	23' 11" (7305 mm)
Max. Digging Reach (Ground)	34' 7" (10 530 mm)
Max Loading Height	23' 10" (7280 mm)
Swing Torque	87,751 lbfft. (12 137 kgf-m)
Arm Digging Force (ISO)	30,644 lbf. (13 900 kgf)
Bucket Digging Force (ISO)	44,092 lbf. (20 000 kgf)
Drawbar Pull	77,162 lbf. (35 000 kgf)
Maximum Auxiliary Hydraulic Flow	2 x 65.5 gpm (2 x 248 L/min)

DOOSAN DELIVERS equipment for tough jobs