

DOOSAN

DX420LC-5 EXCAVATOR

NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- 22' 0" Boom, 10' 8" Arm
- 31.5" (800 mm) Shoes, Rollers (2 upper/9 lower)
- 4 Power Modes / 4 Work Modes
- Telematics — 3 Year Subscription
- Options — Straight Travel, 2-way Aux. Hydraulic Pedal, Diesel Powered Coolant Heater, Plug Heater, Cab Guarding, Additional Work Lamps, Rotate Circuit Piping

NEW MODEL OVERVIEW	DX420LC-5
Rated Power – Gross (hp per SAE J1995)	345 hp (257 kW) @ 1800 rpm
Operating Weight	94,891 lb. (43 042 kg)
Max. Digging Depth	25' 4" (7740 mm)
Max. Digging Reach (Ground)	37' 0" (11 290 mm)
Max. Loading Height	25' 3" (7710 mm)
Swing Torque	118,332 lbf.-ft. (16 360 kgf-m)
Arm Digging Force (ISO)	43,431 lbf. (19 700 kgf)
Bucket Digging Force (ISO)	59,745 lbf. (27 100 kgf)
Drawbar Pull	90,169 lbf. (40 900 kgf)
Maximum Auxiliary Hydraulic Flow	2 x 88.5 gpm (2 x 335 L/min.)

PL-1011-0514

DOOSAN DELIVERS

equipment for tough jobs

*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net. Pictured machine is a DX420LC-3.