

DOOSAN

DX530LC-5 EXCAVATOR

NEW MODEL OVERVIEW



- T4 Emission Compliant (HPCR, CEGR, DOC & SCR)
- 23' 4" Boom, 9' 6" Arm
- 35.4" (900 mm) Shoes, Rollers (3 upper/9 lower)
- 4 Power Modes / 4 Work Modes
- Telematics — 3 Year Subscription
- Options — Straight Travel, 2-way Aux. Hydraulic Pedal, Diesel Powered Coolant Heater, Plug Heater, Cab Guarding, Additional Work Lamps, Rotate Circuit Piping

NEW MODEL OVERVIEW	DX530LC-5
Rated Power – Gross (hp per SAE J1995)	380 hp (283 kW) @ 1800 rpm
Operating Weight	116,576 lb. (52 878 kg)
Max. Digging Depth	24' 1" (7340 mm)
Max. Digging Reach (Ground)	37' 7" (11 455 mm)
Max. Loading Height	25' 4" (7725 mm)
Swing Torque	145,600 lbf.-ft. (20 130 kgf-m)
Arm Digging Force (ISO)	56,879 lbf. (25 800 kgf)
Bucket Digging Force (ISO)	67,902 lbf. (30 800 kgf)
Drawbar Pull	100,531 lbf. (45 600 kgf)
Maximum Auxiliary Hydraulic Flow	2 x 88.5 gpm (2 x 335 L/min.)

PL-1013-0514

DOOSAN DELIVERS

equipment for tough jobs

*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net. Pictured machine is a DX530LC-3.