

DOOSAN®

DX42-5 MINI EXCAVATOR

NEW MODEL OVERVIEW



FEATURES

- T4 Emission Compliant
- 4' 7" (1400 mm) Standard Arm
- 13.8" (350 mm) Rubber Track, Rollers (1 upper/5 lower)
- HVAC, Adjustable Seat and Deluxe Instrumentation

OPTIONS

Canopy, Long Arm, Angle Blade

ATTACHMENT PACKAGE

Quick Coupler, 2-Tine Thumb & 3.92 ft³ (.145 m³) Bucket

NEW MODEL OVERVIEW		DX42-5
Rated Power - Gross (HP per SAE J1995)	hp (kW) @ rpm	42.6 (31.8) @ 2200 rpm
Operating Weight	lb. (kg)	9555 (4334)
Machine Width	ft.-in. (mm)	5' 9" (1750)
Tail Swing Overhang	ft.-in. (mm)	1' 5" (432)
Max. Digging Depth	ft.-in. (mm)	10' 6" (3200)
Max. Digging Reach (Ground)	ft.-in. (mm)	17' 5" (5300)
Max Loading Height	ft.-in. (mm)	12' 2" (3700)
Arm Digging Force (ISO)	lbf. (kgf)	5672 (2573)
Bucket Digging Force (ISO)	lbf. (kgf)	9183 (4165)
Maximum Auxiliary Hydraulic Flow	gpm (L/min)	20 (75.7)
Boom swing	ft.-in. (mm)	75° L / 50° R

*Specifications and design are subject to change without notice. Pictures of Doosan products may show other than standard equipment. All dimensions are shown in inches. For more information refer to Doosan Dealer Net. Pictured machine is a DX42-5.