

NEW MODEL OVERVIEW



FEATURES

- T4 Emission Compliant
- 4' 4" (1330 mm) Standard Arm
- 11.8" (300 mm) Rubber Track, Rollers (1 upper/4 lower)
- HVAC, Adjustable Seat and Deluxe Instrumentation

OPTIONS

Canopy, Long Arm, Angle Blade

ATTACHMENT PACKAGE

Quick Coupler, 2-Tine Thumb and 3.92 ft³ (.145 m³) Bucket "

NEW MODEL OVERVIEW		DX35-5
Rated Power - Gross (HP per SAE J1995)	hp (kW) @ rpm	33.5 (25) @ 2400
Operating Weight	lb. (kg)	8193 (3716)
Machine Width	ft.-in. (mm)	5' 9" (1753)
Tail Swing Overhang	ft.-in. (mm)	0" (0)
Max. Digging Depth	ft.-in. (mm)	10' 2" (3100)
Max. Digging Reach (Ground)	ft.-in. (mm)	17' 1" (5200)
Max Loading Height	ft.-in. (mm)	11' 3" (3437)
Arm Digging Force (ISO)	lbf. (kgf)	4859 (2204)
Bucket Digging Force (ISO)	lbf. (kgf)	6968 (3161)
Maximum Auxiliary Hydraulic Flow	gpm (L/min)	17 (64.4)
Boom swing	ft.-in. (mm)	75° L / 55° R